

▼ From left to right: XC2402MB, XC2302SB



Works with



- Cordless convenience eliminates extension cords, noise and emission producing generators
- High-Performance brushless motor drives high-flow rates for increased productivity and provides twice the life of brushed motors
- Bladder reservoir reduces contamination and allows pump use in any position
- Pump models with 1 gallon oil capacity enable use with larger and multiple cylinders
- Includes shoulder strap SSTRP55, attaches to integrated steel rings for enhanced portability
- Compatible with the Enerpac Connect App, which gives access to the latest tool & job information
- Torque pump models available, see Bolting Tools section.

▼ *Variable Speed Trigger: Featured on manual valve models. Enables greater precision of tool or cylinder travel.*



One gallon reservoir

Pump models with one gallon oil capacity enable use with larger and multiple cylinders.

1 gallon XC2 pump can be used with:

- One **RC10010** 100 tons cylinder
- Two **RC756** 75 tons cylinders
- Three **RC506** 50 tons cylinders
- Four **RC504** 50 tons cylinders

The Next Generation of Cordless Performance and Efficiency



Works with



Use the Enerpac Connect Mobile App for the latest essential tool information. Scanning the QR code on the pump gives instant access to product specifications, manuals, videos, job specific usage data, and wireless firmware updates.



Pendant Controls

Heavy-duty pendants operate any Enerpac XC2-Series pump. Easy to connect or disconnect when not required, the pendants feature

large buttons, an over molded grip, lanyard loop and hanger magnet. Multiple seals within the pendant provide IP64 environmental protection.

Description	Model No.
Pendant, 10 ft cord	CC131
Pendant, 20 ft cord	CC132
Extension Cord, 10 ft	CC010



54 Volt Lithium-Ion Battery

The 4 Ah **EBH544K** battery with high-capacity cells provides extended runtime for higher cycle and larger tool and cylinder applications.



54 Volt Fast Battery Charger

The fast charger minimizes downtime with a 1½ hour charge cycle. Charger provides charge status, over-temperature and damaged battery indication.

54 Volt Fast Charger	Model No.
115 Volt North America	EC1F541B
230 Volt Europe	EC1F542E
230 Volt Australia	EC1F542A

Cordless Hydraulic Pumps



XC2-Series Cordless Pumps

The XC2-Series pumps take speed, battery run time and oil capacity to new levels greatly expanding the usage opportunities. Capable of larger tool and cylinder applications, cordless convenience can be extended further in the field or facility.

The high-performance brushless motor provides the speed of a ½ hp electric pump enabling corded productivity with cordless convenience.

Manual valve models feature a variable speed trigger for greater control of tool or cylinder advance and the Enerpac 54 Volt battery system enables significant work completion on a single battery charge.



Tool / Cylinder	Application	Per Charge
NC5060 Nut Splitter	2.0 inch, A194 Grade 2H Heavy Hex Nut	57x
SP35 Punch	1 ³ / ₁₆ inch hole, ¼ inch mild steel	317x
RCS302 Cylinder	22 tons, 1½ inch extension	43x
RAR506 Cylinder	40 tons, 3.0 inch extension	10½x
RAR1006 Cylinder	80 tons, 3.0 inch extension	4½x

XC2 Series



Reservoir Capacity:
134 - 256 in³


Flow at Rated Pressure:
20 in³/min

Motor & Battery Size:
0.94 hp, 54 V / 4 Ah


Maximum Operating Pressure:
10,000 psi

- ① Outlet "Advance" Port 3/8"-18 NPTF
- ② Inlet "Retract" Port 3/8"-18 NPTF *
- ③ Pendant connection port
- ④ User Adjustable Relief Valve Access
- ⑤ Directional Control Valve **
- ⑥ Shoulder Strap Connection Points
- ⑦ Trigger Lock **
- ⑧ Variable speed trigger **
- ⑨ Oil Fill (must use funnel)

* On Double-Acting models
** On Manual Valve models



OIL FLOW vs. PRESSURE



SELECTION CHART

Pump Type (Used with cylinder)	Useable Oil Capacity (in³)	Model Number ¹⁾	Output Flow Rate (in³/min)		Valve Function	Pendant in kit	Batteries in kit	Charger in kit	Weight ²⁾ (lbs)
Single-Acting	122	XC2202M	160	20	Manual 3-way, 2-position	—	—	—	26.3
	241	XC2204M				—	—	—	29.8
	122	XC2202MB				—	2x 4 Ah	115 V	26.3
	241	XC2204MB				—	2x 4 Ah	115 V	29.8
Single-Acting	122	XC2302S	160	20	Solenoid 3-way, 2-position	CC131	—	—	28.3
	241	XC2304S				CC131	—	—	31.8
	122	XC2302SB				CC131	2x 4 Ah	115 V	28.3
	241	XC2304SB				CC131	2x 4 Ah	115 V	31.8
Double-Acting	122	XC2402M	160	20	Manual 4-way, 3-position	—	—	—	28.3
	241	XC2404M				—	—	—	31.8
	122	XC2402MB				—	2x 4 Ah	115 V	28.3
	241	XC2404MB				—	2x 4 Ah	115 V	31.8

¹⁾ Pumps available with 230 V North European plugset charger. Substitute "B" suffix with "E" in model number. Example: XC2204ME.

Pumps available with 230 V Australian plugset charger. Substitute "B" suffix with "A" in model number. Example: XC2304SA.

²⁾ Weight includes pump with oil and battery. Battery weight 3.5 lbs.