

Tool Lubricants

Oils and Greases

By lubricating your air tools, you will prolong the life of tool motors, mechanisms, gearing, and other vital parts. Ingersoll Rand offers a complete line of specialised oils and greases that are engineered specifically for the use with air tools.



Part no.	No.	Description / Recommended use	Capacity
Greases			
23-1 LB	23	For the gearing of drills	0.45 kg
28 1 LB	28	For screwdriver gearing and clutches, drills, grinders, saws, tie tamper grease	0.45 kg
66 1 LB	66	For slow-speed, high-torque angle heads	0.45 kg
67-4T	67	For high-speed, high-temp angle heads (green)	0.12 l tube
67-1 LB			0.45 kg
68-1LB	68	For coupling splines and high speed angle heads	0.45 kg
70 1 LB	70	For large-piston motors and gear cases	0.45 kg
80 1 LB	80	For bearings on sump pumps	0.45 kg
80 8 LB			3.60 kg
100 1 LB	100	For standard-duty impact wrenches	0.45 kg
100 8 LB			3.60 kg
105-4T-6	105	For metallic housing impact wrenches	6 tubes of 0.12 l
105-1LB			0.45 kg
105-8LB			3.60 kg
115-4T	115	For composite housing impact wrenches	0.12 l tube
115-1LB			0.45 kg
150 8 LB	150	For impact mechanisms with swinging weight	3.60 kg
170-1 LB	170	Premium impact grease for high temperatures, used with impact mechanisms	0.45 kg
Air Lubricating Oils			
10Z4	—	For use with percussive, assembly, and impact wrenches	0.12 l
10P	—		0.50 l
10G	—		3.80 l
10GW	—	Oil and antifreeze for use with percussive, assembly, and impact wrenches	3.80 l
50P	—	For use with grinders, impact wrenches, hoists, and winches	0.50 l
50G	—		3.80 l
Lubri-Link Green	—	Unique U.S.D.A. accepted food grade chain lubricant	0.50 l

Lubrication Kits and Accessories

Part no.	Description / Compatible tools
Lubrication Kits	
67-LBK1	80 g grease, 110 g oil and grease tube
105-LBK1	gun head
115-LBK1	gun head
Grease Guns	
P25-228	Push-type hand gun for hydraulic-type fittings
R000A2-228	Push-type hand gun for flush-type fittings
GTH-1	Grease gun used with Ingersoll Rand 0.12 l tube of
Lubricants for VORTEX Turbine Grinder	
VT22-SK1 ⁽¹⁾	lubricant kit (250 ml of oil + syringe)

(1) Note: VT22-T24 spindle lock key is required for oil change.

